



VOLTAGE CHART

PART OF
IV100
VSP9407

- SCHEMATIC NOTES
1. RESISTOR VALUES ARE IN OHMS, K=1,000, M=1,000,000. RESISTOR ARE 0.5W 5% UNLESS OTHERWISE INDICATED.
 2. CAPACITANCE VALUES 1.0 AND ABOVE ARE IN PF. VALUES BELOW 1.0 ARE IN PICO. CAPACITORS ARE 50V UNLESS OTHERWISE INDICATED.
 3. ↓ DENOTES CHASSIS GROUND. ⊕ DENOTES ISOLATED GROUND.
- ⚡ INDICATES ESD SENSITIVE COMPONENT.
- ⚡ INDICATES ZERO OHM CHIP COMPONENT.

ALL INTEGRATED CIRCUITS AND MANY OTHER SEMICONDUCTOR COMPONENTS ARE ELECTROSTATICALLY SENSITIVE AND REQUIRE SPECIAL HANDLING TECHNIQUES TO PREVENT DAMAGE. SEE THE SAFETY AND SERVICE PRECAUTIONS PUBLICATION.

PRODUCT SAFETY NOTE
COMPONENTS WITH A ⚡ WIRE SPECIFICATION ARE ESD SENSITIVE. THESE COMPONENTS READ CAREFULLY THE PRODUCT SAFETY NOTICE IN THIS SERVICE DATA DO NOT DEGRADE THE SAFETY OF THE SET THROUGH IMPROPER SERVICING.

SERVICE NOTICE