DEFLECTION SCHEMATIC – VERTICAL/PROCESS (1 OF 2)

181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200

A B C D E F G H I J K L

FROM XRP_ALIGN

FROM +12V_SENSE

PART OF U14801

PART OF U14801

U14802 DEFLECTION PROCESSOR

U14501 VERTICAL OUTPUT

PWR AMP

GEN FB

M000 M001 M002 M003 M004 M005 M006 M007 M008 M009 M010 M011

Q14802 Q14803 Q14804 Q14805 Q14806 Q14901 Q14902 Q14903 Q14904 Q14905 Q14501 Q14502 Q14906

CR14801 CR14802 CR14803 CR14900 CR14501 CR14502 CR14503 CR14504 CR14505

RN14501

L14501 L14502

RT14501

J14901

TO EW_FB

TO XRP_SENSE

TO XRP_LATCH

TO J14901

TO SCAN_V

TO BEAM_SENSE1

TO VYOKE_HI

TO VDF

TO BLK_OUT

TO HDF

TO VYOKE_LO

TO DF_BLANK

TO H_CURVE

ALL INTEGRATED CIRCUITS AND MANY OTHER SEMICONDUCTORS ARE ELECTROSTATICALLY SENSITIVE AND REQUIRE SPECIAL HANDLING TECHNIQUES DESCRIBED UNDER "ELECTROSTATICALLY SENSITIVE (ES) DEVICES" IN THE SAFETY AND SERVICING PRECAUTIONS PUBLICATION.

PRODUCT SAFETY NOTE

COMPONENTS WITH A ⚠ HAVE SPECIAL CHARACTERISTICS IMPORTANT TO SAFETY. BEFORE REPLACING ANY OF THESE COMPONENTS READ CAREFULLY THE PRODUCT SAFETY NOTICE IN THIS SERVICE DATA. DO NOT DEGRADE THE SAFETY OF THE SET THROUGH IMPROPER SERVICING.

SCHEMATIC NOTES

1. RESISTANCE VALUES ARE IN OHMS; K=X1000, Meg=X1,000,000.
   RESISTORS ARE 1/4W 5%, EXCEPT WHERE INDICATED.
   [ ] INDICATES FLAT MAXI-CHIP COMPONENT, 1/8W EXCEPT WHERE INDICATED.
   / \ INDICATES FLAT MINI-CHIP COMPONENT, 1/16W EXCEPT WHERE INDICATED.
2. CAPACITANCE VALUES 1.0 AND ABOVE ARE IN pF, VALUES BELOW 1.0 ARE IN µF, EXCEPT WHERE INDICATED. VOLTAGE RATING IS 50V EXCEPT WHERE INDICATED.
   [ ] INDICATES FLAT MAXI-CHIP COMPONENT.
   / \ INDICATES FLAT MINI-CHIP COMPONENT.
3. ⏚ DENOTES CHASSIS GROUND. ⊙ INDICATES CONNECTION VIA POINT-TO-POINT WIRE.
   —INDICATES JUMPER WIRE.
   —INDICATES ZERO OHM CHIP COMPONENT.

PAGE 9–10