


ALL INTEGRATED CIRCUITS AND MANY OTHER SEMICONDUCTORS ARE ELECTROSTATICALLY SENSITIVE AND REQUIRE SPECIAL HANDLING TECHNIQUES DESCRIBED UNDER "ELECTROSTATICALLY SENSITIVE DEVICES" IN THE USER'S SERVICE PRECAUTIONS PUBLICATION.

PRODUCT SAFETY NOTE
COMPONENTS WITH A  WIRE SPECIFICATION ARE ESSENTIALLY SENSITIVE AND REQUIRE THESE COMPONENTS READ CAREFULLY THE PRODUCT SAFETY NOTICE IN THIS SERVICE DATA DO NOT DEGRADE THE SAFETY OF THE SET THROUGH IMPROPER SERVICING.

- SCHEMATIC NOTES
- RESISTOR VALUES ARE IN OHMS; K=X1,000; M=X1,000,000. RESISTORS ARE 5% EXCEPT WHERE INDICATED.
 - INDICATES FLAT MAXI-CHIP COMPONENT; 1/8W EXCEPT WHERE INDICATED. INDICATES FLAT MINI-CHIP COMPONENT; 1/16W EXCEPT WHERE INDICATED. CAPACITANCE VALUES 1.0 AND ABOVE ARE IN P.F., VALUES BELOW 1.0 ARE IN P.F.
 - INDICATES FLAT MINI-CHIP COMPONENT.
 - ↓ DENOTES CHASSIS GROUND. ○ INDICATES CONNECTION VIA POINT-TO-POINT WIRE.
 - INDICATES JUMPER WIRE.
 - INDICATES ZERO OHM CHIP COMPONENT.

TO SCL
TO SDA