


MODEL 20T775MH SCHEMATIC DIAGRAM



NOTES

1. RESISTOR VALUES ARE IN OHMS K=1000 M=1,000,000
2. ALL RESISTORS ARE 1/4WATT EXCEPT WHERE OTHERWISE INDICATED.
3. CAPACITOR VALUES ARE IN P.F. UNLESS OTHERWISE INDICATED. P-PF
4. ALL CAPACITORS ARE SOVOLT EXCEPT WHERE OTHERWISE INDICATED.
5. VOLTAGES AND WAVEFORMS MEASURED UNDER AVERAGE COLOR SIGNAL INPUT AND CONTRAST, BRIGHTNESS, CONTROL AT MAXIMUM.
6. @----- HORIZONTAL RATE. @----- VERTICAL RATE.

WARNING

REPLACEMENT PARTS WHICH HAVE SPECIAL SAFETY CHARACTERISTICS ARE IDENTIFIED BY * SHADING ON THE SCHEMATICS. REPLACE THESE CRITICAL COMPONENTS WITH RECOMMENDED REPLACEMENT PARTS. DON'T DEGRADE THE SAFETY OF THE SET THROUGH IMPROPER SERVICING.

CONTROL IS MARKED * IS PERMANENTLY FROZEN. DO NOT ATTEMPT TO DEFEAT OR IMPROPERLY REPLACE.