

## **SPECIFICATIONS**

Power Input: .....	120 Volts AC 60Hz
Power Consumption: .....	17 Watts (2-head and 4-head)
Operating Temperature: .....	5 degree C to 40 degree C (41 degree F to 104 degree F)
Storage Temperature: .....	-30 degree C to 65 degree C (-22 degree F to 149 degree F)
Weight: .....	3.6 kg
Dimensions: .....	360mm Wide X 90mm High X 278mm Deep
Recording System: .....	4-head: Four video record/playback heads Rotary helical scan/luma: FM recording/chroma: converted subcarrier phase shifted recording 2-head: Two video/playback heads Rotary helical scan/luma: FM recording/chroma: converted subcarrier phase shifted recording Video head
Video Signal: .....	EIA standard; NTSC color
Antenna: .....	75 ohm input impedance
Video Signal Level: .....	1Vp-p (140 IRE standard)
Audio Input Impedance: .....	47k ohms
Audio Output Impedance: .....	Less than 1.5k ohm
Tape Speed: .....	SP: 33.35mm/sec. SLP: 11.13mm/sec.
Maximum Recording Time: .....	T-60: 3 hours/SLP mode T120: 6 hours/SLP mode
Fast Forward/Rewind Time: .....	3 minutes (T-120 tape)
Tuning System: .....	Auto Program/Cable Compatible/Frequency Synthesis (FS)

\*Specifications are subject to change without notice.