

VR636HF/VR645HF/VG4268
SPECIFICATIONS

Power Input:	120 Volts AC 60Hz
Power Consumption:	19 Watts (4-head Hi-Fi)
Operating Temperature:	5 degree C to 40 degree C (41 degree F to 104 degree F)
Storage Temperature:	-30 degree C to 65 degree C (-22 degree F to 149 degree F)
Weight:	3.6 kg
Dimensions:	360mm Wide X 90mm High X 278mm Deep
Recording System:	4-head Hi-Fi: Four video record/playback heads. Rotary helical scan/luma: FM recording/chroma: converted subcarrier phase shifted recording. Two audio record/playback heads. Rotary helical scan, 2 channels FM recording.
Video Signal:	EIA standard; NTSC color
Antenna:	75 ohm input impedance
Video Signal Level:	1Vp-p (140 IRE standard)
Audio Input Impedance:	47k ohms
Audio Output Impedance:	Less than 1.5k ohm
Tape Speed:	SP: 33.35mm/sec. SLP: 11.13mm/sec.
Maximum Recording Time:	T-60: 3 hours/SLP mode T120: 6 hours/SLP mode
Fast Forward/Rewind Time:	3 minutes (T-120 tape)
Tuning System:	Auto Program/Cable Compatible/Frequency Synthesis (FS)

*Specifications are subject to change without notice.